

# Technical features

## Digital clock

**Cristalys Date**

### Description :

- ▶ Indoor clock with liquid crystal display (LCD).
- ▶ Hour and multilingual date display, with temperature, day countdown.
- ▶ Extra flat casing.
- ▶ Readability 25 metres, angle of vision 160°.
- ▶ Power supply with 4 LR 14 batteries for an autonomy over 3 years.
- ▶ Versions : independent quartz, radio synchronised FI or DCF, DHF receiver, slave movement on impulses or IRIG B/AFNOR coded time receiver.



### Technical features :

- ▶ Eco function providing energy savings through switching off display between 23.00 and 6.00.
- ▶ Multifunctional display.
- ▶ Display in a choice of 18 languages.
- ▶ 12 or 24 hour display mode.
- ▶ Pre-programmed automatic summer/winter time changeover and perpetual calendar with multi-time zones.
- ▶ Permanent data saving.
- ▶ Accuracy of the time quartz base : 0,2 second/day.
- ▶ Absolute time accuracy with optional radio synchronisation.
- ▶ ABS casing, IP40.
- ▶ Silent operation.
- ▶ Programming and time setting through 2 buttons.
- ▶ Optional very low voltage power supply from 6 to 24V AC/DC (or external 230V).
- ▶ Operating temperature: from 0 to 50°C.
- ▶ Humidity: 80% at 40°C.
- ▶ Weight: 1,4 Kg.


### Multifunctional clock :

*Possibility for fixed or alternate display on the central display line :*


- ▶ Day of the week multilingual.
- ▶ Ambient temperature in Celsius or Fahrenheit (limited to 99°).
- ▶ Day number (Julian).
- ▶ Week number.
- ▶ Second counter.

*Possibility for fixed or alternate display on the bottom display line :*

- ▶ Multilingual date.
- ▶ Numerical date.
- ▶ Site or city name or a word (up to 7 characters).
- ▶ Day countdown.



**4 casing colours:  
aluminium,  
champagne,  
burgundy, white**



**France Inter or  
DCF transmitter**

### Cristalys Date references

- |  |         |
|--|---------|
| ▶ Independent quartz   | 938 211 |
| ▶ Radio synchronised France Inter  | 938 221 |
| ▶ Radio synchronised DCF   | 938 223 |
| ▶ Slave movement on impulses or IRIG B/AFNOR receiver                    | 938 231 |
| ▶ Slave movement on impulses or IRIG B/AFNOR receiver (very low voltage) | 938 232 |
| ▶ DHF radio receiver   | 938 241 |
- Add to the reference: A for aluminium casing colour, B for white, C for champagne, D for burgundy.



**Bodet**

# Technical features

## Digital clock

## Cristalys Date



Cristalys Date  
on table support



Cristalys Date  
on double sided  
bracket

### Movements and synchronisation:

#### Quartz movement

- ▶ The clock is totally independent, the time information comes from its own time basis.
- ▶ Automatic summer/winter time changeover.

#### DHF movement

- ▶ The clock is radio-synchronised by a DHF transmitter.
- ▶ Automatic summer/winter time changeover.

#### FI or DCF Radio synchronised movement

- ▶ The clock is independent, the time information comes from its own time basis which is rectified, in case of drift, by comparing it to the FI or DCF transmitter signal.
- ▶ The radio synchronisation permit to display the time with perfect accuracy.
- ▶ Automatic summer/winter time changeover.

#### IRIG B/AFNOR coded time receiver

- ▶ The coded time distribution consist in transmitting a complete time message each second : the setting on time of the receivers is realised automatically and speedily as soon as they are connected on the clock line.
- ▶ The IRIG B/AFNOR coded time does not transmit interference and is insensitive to other electrical interference.



#### 24V minute impulses receiver movement

- ▶ The receiver clocks are connected to a distribution line and activated by means of electrical impulses transmitted every minute by the master clock.

### Norms :

- ▶ Norm NF EN50081-1 : generic emission standard.
- ▶ Norm NF EN50082-1 : generic immunity standard.
- ▶ Norm NF EN60950 : safety of information technology equipment.

### Dimensions in mm



### Options:

- ▶ Wall support (supplied with each Cristalys clock) 202 271
- ▶ Table support 938 902
- ▶ Double sided bracket for wall or ceiling mounting 938 901
- ▶ Double sided bracket for wall or ceiling mounting (long length) 938 905
- ▶ Single or double sided bracket specific length for wall or ceiling mounting 938 908  
(Please specify on the order the fixing mode (wall or ceiling) and the length between the top of the clock and the fixing point).
- ▶ Support for very low voltage power supply. 938 907
- ▶ Plug-in mains adapter 230V/15V (Capacity: 20 clocks). 938 912

